



ACCENDO
LIGHTING



General Description:

The Accendo Lighting wet location all LED exit and emergency polycarbonate combo series of exit signs is designed to be a cost effective and superior quality answer to your emergency and egress lighting needs. Specially designed for areas where moisture penetration is a high concern. The wet location exit features a five year warranty on the housing and can be ordered with custom lettering on the faces.

Features:

- Long lasting, efficient, ultra bright white LED lamp heads.
- 3.6 watt (3 LEDs x 1.2 watt) per head.
- Adjustable LED lamp heads provide optimal center-to-center spacing.
- Long-life, energy efficient Red or Green LED EXIT sign illumination.
- Dual 120/277V.
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery).
- 6V long life, maintenance free, rechargeable NiCd battery. Internal solid-state transfer switch automatically connects the internal battery to LED board and lampheads for minimum 90-minute emergency illumination.
- Fully automatic solid state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Die-cast aluminum mounting canopy included for top or end mount
- Universal knockout pattern on back plate for wall mount.
- 5VA flame retardant, UV stabilized polycarbonate in white, black or gray finish.
- High-impact resistant, UV stabilized polycarbonate clear lens.
- Corrosion resistant enclosure with engineering grade silicone gasket.
- Knockout's provided for conduit feed applications.
- EZ snap-out Chevron directional indicators.
- RC: Remote capacity up to 7.2 watts.
- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.
- CW: Optional internal heater and battery blanket for extreme cold temperature applications (-20° C – 50° C).

Warranty & Listings:

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL listed for wet locations (0°C – 50°C).
- Certified to CEC under title 20 regulations.

Ordering Information

Ordering Example: ALEXVWC-1-R-W-RC

Series	No. of Faces	Letter Color	Housing Color	Options
ALEXVWC	1 - single 2 - double	R - Red G - Green	W - White B - Black G - Gray	RC - Remote Capacity SDT - Self Test Diag. TP - Tamper-Proof CW - Cold Weather CUST - Custom Wording

STANDARD



OPTIONAL



Dimensions:

AL EM-Series
Rough Service/Wet Location Combo

