



**ACCENDO**  
LIGHTING



### General Description:

The Retrofit LED Cover Kit C is used to convert fluorescent T8 industrial strip fixtures to LED which results in substantial energy savings and improved lighting. The Retrofit LED Cover Kit can easily produce ideal IES recommended light levels with minimal energy consumption. Accendo retrofit kits will continue to provide consistent fixture performance and repeat annual energy savings for many years to come.



### FEATURES

- Considerable reduction in energy costs as compared to open strip fluorescent fixtures.
- Significant reduction in maintenance costs and easily cleaned.
- Streamlined packaging for easy job site management and easy installation in the field.
- Retrofit existing strip channels from HO or slimline to F32 T8 or F54 T5HO.
- Adjustable raceways (4.25"/5.00").
- Heavy duty steel construction.
- Custom configurations and widths available.
- Suitable for retail, manufacturing or warehousing.

### CONSTRUCTION

- Driver/ballast covers are precision formed 22 gauge steel, 4.25" or 5.00" wide, painted white. 8 ft. kit includes a one piece 8 ft. long driver/ballast cover.
- Lampholders mount directly to driver/ballast covers.
- Kit includes: driver/ballast cover, optional lampholders, tek screws, and quarter turn fasteners.
- 22 gauge steel painted white.
- Precision formed to fit over the existing strip channel.
- Tek screws and ballast mounting hardware included.

### ELECTRICAL

- Choice of shunted or unshunted lampholders. If pre-wired assembly kit is ordered separately, lamp holders will be included in the wiring.
- Lampholders are high profile snap-in rotating camlock design.
- LED tubes not included (sold separately).

### WARRANTY

- Backed by Accendo's 5-year limited warranty.

### APPLICATIONS

- Relamping 4' or 8' fluorescent strip fixtures to one, two or four T8 LED tubes, most common in industrial or commercial spaces.

### Ordering Information

Ordering Example: ALRCKC-4-02-32-C-ADJ-425-RS-XLS

|        | Size    | No. LAMPS     | LAMP TYPE   | OPTICS     | BRACKET TYPE                     | CHANNEL WIDTH | Series                     | Series |
|--------|---------|---------------|-------------|------------|----------------------------------|---------------|----------------------------|--------|
| ALRCKC | 4 4 ft. | 01 1 T8 Lamp  | 32 F32 T8   | C Design C | ADJ Adjustable<br>4.25" or 5.00" | 425 4.25"     | RS Unshunted<br>Lampholder | XLS    |
|        | 8 8 ft. | 02 2 T8 Lamps | 54 F54 T5HO |            |                                  | 500 5.00"     |                            |        |
|        |         | 03 3 T8 Lamps |             |            |                                  |               |                            |        |
|        |         | 04 4 T8 Lamps |             |            |                                  |               |                            |        |

Additional:

DIMENSIONS

